





Foret SDS-MAX extrême 4 taillants



Caractéristiques produits

Conditionnement

Emmanchement SDS Max

Unité de vente (1 conditionnement)

Caractéristiques techniques

Code	Diamètre (mm)	Longueur utile (mm)	Longueur totale (mm)
252492	16	200	340
252499	16	400	540
252506	18	200	340
252513	18	400	540
252527	20	400	540
252534	20	800	920
252541	22	200	340
252548	22	400	540
252555	22	800	920
252562	24	200	340
252569	24	400	540
252576	25	400	540
252583	25	800	920
252590	26	400	540
252604	28	450	570
252611	28	550	670
252618	30	450	570
252625	32	250	380
252632	32	450	570
252639	32	800	920









Code	Diamètre (mm)	Longueur utile (mm)	Longueur totale (mm)
252646	35	450	570
252653	35	550	670
252660	36	450	570
252667	38	450	570
252681	40	800	920
252688	42	450	570
252695	45	450	570
252702	50	450	570
252709	52	450	570
252520	20	200	340
252597	28	250	380
252674	40	450	570





Descriptif

Les forets SDS-max EXTREME possèdent deux taillants en carbure pour un perçage rapide et efficace

Les quatres hélices permettent une évacuation rapide des débris pour un perçage optimale.

Conditions de livraison

Carton