

## ▶ Réduction cuivre M/F à souder 243CU



p. 3-314

### Caractéristiques produits

Installation	<b>Réseau sanitaire et chauffage</b>
Type de raccord	<b>Réduction</b>
Type de raccordement	<b>À souder</b>
Type d'embout	<b>Mâle-Femelle</b>
Unité de vente	<b>(1 conditionnement)</b>


### Caractéristiques techniques

Code	Conditionnement	Diamètre (millimètre (mm))
710445	1	16-10
710094	1	12-10
710099	1	18-12
710266	1	22-12
710108	1	28-22
710446	1	28-12
710105	1	28-14
710106	1	28-16
710107	1	28-18
710447	1	35-18
710448	1	35-22
710109	1	35-28
710264	1	40-28
710449	1	42-22
710271	1	42-28
710110	1	42-35
710265	1	54-28
710452	1	54-35
710111	1	54-42

Code	Conditionnement	Diamètre (millimètre (mm))
710207	1	32-28
710208	1	40-32
710206	1	32-22
699254	10	22-18
699247	10	22-16
699240	10	16-14
699212	10	14-12
699219	10	16-12
699226	10	18-14
699233	10	18-16
699443	10	22-14
239936	1	16-12
239859	1	14-12
239866	1	16-14
239873	1	18-14
239880	1	18-16



### Produits complémentaires



Coude cuivre  
90° F/F à  
souder 90CU



Manchon  
cuivre égal F/F  
à souder  
270CU



Manchon à  
souder mâle à  
visser  
243GCU



Mamelon  
laiton égal  
M/M à visser